

Pair, Twin, Triple, double twin

RZQ-C



Inverter



Auto cooling-heating
changeover

Packaged system for commercial applications

- › Available as 20 and 25kW
- › Re-use of existing R-22 or R-407C technology
- › Guarantees operation in heating mode down to -15°C
- › Standard night quiet mode
- › Maximum piping length up to 100m
- › Wide range of connectable indoor units

RZQ-C

Packaged systems for commercial applications



RZQ200-250C7Y1B

Pair application

capacity class	FDQ-B	
	200	250
RZQ200C	1	
RZQ250C		1


Twin, triple and double twin application

capacity class	FCQG-F					FFQ-C		FDXS-F(9)			FBQ-D				FHQ-C				FUQ-C			FAQ-C		FDQ-C		FNQ-A	
	50	60	71	100	125	50	60	50	60	50	60	71	100	125	50	60	71	100	125	71	100	125	71	100	125	50	60
RZQ200C	4	3	3	2		4	3	4	3	4	3	3	2		4	3	3	2		3	2		3	2		4	3
RZQ250C		4			2		4		4		4			4		2			2			2			2		4

Outdoor unit			RZQ	200C	250C
Dimensions	Unit	HeightxWidthxDepth	mm	1,680x930x765	
Sound power level	Cooling		dBA	78	
	Heating		dBA	78	
Sound pressure level	Nom.		dBA	57	
Operation range	Cooling	Ambient	Min.~Max.	°CDB -5.0~46.0	
	Heating	Ambient	Min.~Max.	°CWB -15.0~15.0	
Refrigerant	Type/Charge/GWP		kg/TCO ₂ eq	R-410A/8.3/17.3/2,087.5	R-410A/9.3/19.4/2,087.5
Power supply	Phase/Frequency/Voltage		Hz/V	3N~/50/380-415	

Sound power level is an absolute value that a sound source generates. | Sound pressure level is a relative value, depending on the distance and acoustic environment. For more details, please refer to the sound level drawings. | Sound values are measured in a semi-anechoic room. | Power supply to the FDQ indoor unit is separate | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-127

01/16



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

The present publication supersedes ECPEN15-127